



PRODUCT DATASHEET

LED FACADE LIGHT (FLOOD TYPE)



| | | | | |
|-----------------------|-------------------------------|---------------|---------------|---------------|
| Product Code | NE1702-50W | NE1702-100W | NE1702-150W | NE1702-200W |
| Input Power (W) | 50W | 100W | 150W | 200W |
| LED Type | EDISON ES RGB | EDISON ES RGB | EDISON ES RGB | EDISON ES RGB |
| Beam Angle | 30°/60°/90°/120° Degree | | | |
| CRI (%) | ≥ 80 | | | |
| LED CCT | 3000K, 4000K, 6500K / RGB | | | |
| System Efficiency (%) | > 90 | | | |
| Operating Voltage (V) | 100-265 VAC @ 50-60 Hz | | | |
| Power Factor (Φ) | > 0.95 | | | |
| THD (%) | < 10 % | | | |
| Surge Protection | Up to 6 KV | | | |
| Driver Topology | Constant Voltage | | | |
| Controller Type | IR/RF/WIFI/DMX | | | |
| Operating Temperature | 0° to + 50° C | | | |
| Housing Material | Aluminum Pressure Die casting | | | |
| Optical Cover | Glass + Lens | | | |
| IP Rating | IP65 | | | |

